



GREAMARK E-4/L-4 Articulated Dump Truck (ADT) Tire

The GREAMARK E-4/L-4 Articulated Dump Truck (ADT) Tire is engineered to tackle the harshest conditions of mining, construction, and large-scale earthmoving projects. Its wide, robust tread design and flexible carcass deliver exceptional traction and stability on uneven terrain, while specialized reinforcement ensures resistance to cuts, punctures, and abrasions—perfectly aligning with the brand’s “Run Over the Tough” commitment to reliable performance in complex working environments.

Usage of Application

-  Articulated dump trucks (ADTs) for heavy material transport in open-pit mines
-  ADTs operating in construction sites for earthmoving and debris hauling
-  Heavy-duty ADTs working on rough, muddy terrain in infrastructure projects
-  Construction ADTs used in road-building and land-development tasks



Product Specifications

Parameter	26.5R25	29.5R25
Size	26.5R25	29.5R25
TRA	E-4 / L-4	E-4 / L-4
TT / TL	TL	TL
Tread Depth (mm)	54	58
Standard Rim	22.00/3.0	25.00/3.5
Overall Diameter (mm)	1750	1874
Section Width (mm)	673	749
Load Index / Speed Symbol	193B / 209A2	200B / 216A2
Max Load (50 km/h) (Kg)	11500	14000
Max Load (10 km/h) (Kg)	18500	22400
Inflation Pressure (50 km/h) (kPa)	525	525
Inflation Pressure (10 km/h) (kPa)	650	650
Star Rating	★★	★★